



Denso Tape Technical Data Sheet

Anti-Corrosion Petrolatum Tape

Conformable, Cold-Applied Fabric Tape for the Corrosion Protection of Pipes

Composition: Durable synthetic fibre fabric impregnated and coated with a petrolatum compound.

Uses: Denso Tape is used for the corrosion protection of buried or exposed pipes, valves, and fittings.

Sizes Offered

- Widths: 50mm, 75mm, 100mm, 150mm, 300mm
- Length: 10 Metre Rolls



Benefits

- Resistant to water, water vapour and gases
- Resistant to mineral acids, alkali and salts
- Non-hardening, non-cracking
- Conformable over a wide temperature range

Technical

- **Breaking Strength:** 200 N/50mm minimum
- **Elongation at Break:** 10%
- **Breakdown Voltage:** 16kV minimum per double layer
- **Total Thickness :** 1.15 mm
- **Weight:** 1.44 kg/m²
- **Service Temperature:** -20°C to + 55°C

Get in touch with the Affixit Team Today to find your perfect solution or visit <https://www.affixit.co.uk/denso-tape.html> for further information.

Unit 6 Lime Grove Estate, Haverhill, Suffolk, CB9 7XU

Tel: 01440 765 515 Email: sales@affixit.co.uk

The details and information given in this literature are based on best current knowledge. They are intended to serve as general information only and it is advised that the user conducts their own tests for their specific set of conditions to determine the suitability of the product for its proposed use. No warranty or liability is given or implied regarding any part of these instructions or details, or the completeness of the information. We reserve the right to modify, or change, the specifications and information without advance notification. All goods are supplied subject to our standard conditions of sales, copies of which are available upon request.