

LYN9150R

HIGH PERFORMANCE REVERSE WOUND ATG TAPE



GENERAL DESCRIPTION

125 micron modified acrylic adhesive wound on a brown siliconized paper release liner. Designed for mounting various materials as fabrics, paper, plastic films, metal foils, cardboard, glass, etc. Reverse wound on 1" plastic core to be used in the Affixit ATS-100 gun dispenser.

FEATURES

- Very high tack and adhesion
- Good shear strength and ageing resistance
- Quick and easy to use
- Acid free

APPLICATIONS

- Paper and plastic industry, flying splices, core starting, end-tapping, packaging, etc.
- Laminations of fabrics and foam, mounting of displays, photo, posters, leaflets, etc.

TECHNICAL DATA

Property	Value
Product Type	Double coated
Backing Type	Transfer
Adhesive Type	Modified acrylic
Color	Translucent
Liner Type	Bi-siliconized paper
Liner Color	Brown
Total Thickness	0,12 mm
Peel Adhesion at 180° On Steel	9.00 N/cm
Peel Adhesion at 90° On Steel	7.00 N/cm
Rolling Ball Tack	< 10 cm
Static Shear	168 hrs
Short Time Temperature Resistance	140 °C
Temperature Resistance	-30°C/+110 °C
Shelf Life	12 months
Standard Length	16,5-33 m
Standard Width	6-9-12-19 mm

* International harmonized test methods: ASTM D-1000, PSTC, EN 60454-2.

The ingredients of the adhesive used in this product meet the compositional requirements of the FDA (21 C.F.R. paragraph 175.105) and can be used in indirect food contact only in conjunction with an impermeable functional barrier. Please remember that the user is responsible for determining if the final application complies with applicable laws and regulations.



AFFIXIT
Unit 6 Lime Grove Estate
Haverhill, Suffolk
CB9 7XU
Tel: 01440 766 975
Sales@affixit.co.uk
www.affixit.co.uk

All statements and information listed above regarding this product are typical values for general guidance; these data are not to be intended as a conformity specification. These suggestions are based on tests believed to be reliable, but accuracy and completeness are not guaranteed. The user must test, evaluate and validate this product before use, assuming all risks and liability of such use. This document may be revised without prior notice. Suggested storage conditions: 10°C–30°C, 50% relative humidity.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Lynvale Ltd products for all intended uses, and that the materials to be used comply with all applicable regulatory requirements. Lynvale Ltd (trading as Affixit) assumes no responsibility for product failures arising from misuse of the materials it supplies, or from the design, fabrication or application of products into which the materials are incorporated.

WARRANTY: For a period of 12 months, Lynvale Ltd warrants this product to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or, at Lynvale Ltd's option, to refund the purchase price thereof. LYNVALE LTD DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.